

---

Name: Manual Softener Valve TMF64A

Model: TMF64A

Product introduction:



**Patent No.:** ZL02220153.X ZL200420078956.5

**Certificate:** CE ROHS

China Boiler Association Registration No.:WA1111001

**Technical Parameter:**

Controller model: Manual / Down-flow

Suited pressure: 0.1 - 0.6MPa

Suited water temperature: 5-45°C

Water Capacity: 4.5t/h

Tank Diameter Range for Softens: 6"-18"

Water Inlet/Outlet: 1"F (Inner tooth)

Drain: 1/2"M (Outer tooth)

Brine Tank Connection: 3/8"M (Outer tooth)

Rinse Pipe: 1.05"OD (26.7mm)

Base (The connector for tank): 2-1/2" 8NPSM

**Features:**

- 1)Adopt the high degree pottery, seal slice with scuff resistance, corrosion proof, perfect sealing, and long time for using.
- 2)Manual operate directly realize regeneration immediately.

- 
- 3)Cleaning the ejection nozzle automatically when adding water, to prevent block.
  - 4)No coming water while single pot type control valve regeneration.
  - 5)When do not need soften function, block ejection nozzle could do purifier treatment.

**Rang of Application:**

- 1)Household purify, soften system.
- 2)Boiler softening water system.
- 3)Ro pre-treatment system.
- 4)Swimming pool filters equipment.
- 5)Ion exchange equipment.

**Package:** 20 PCS/CTN